

## T 13-125 (600431420) Diamond cutting system (110-120 V / AC/DC 0/50/60 Hz); MetaLoc

Order no. 600431420

EAN 4061792176164



Product may differ from Image



- Compact diamond cutter for low-dust dry cuts up to 27 mm in mineral materials
- Efficient dust extraction for health protection and clean construction sites
- Metabo Long-life motor with patented dust protection for long service life
- Universal use with pushing cut and plunge function
- Precise cuts on even surfaces thanks to metal base plate with rollers. Removable for free-hand cuts
- Can be used with guide rail for long, straight cuts
- Safety and control in any situation: S-automatic safety clutch and restart protection
- Extraction hood can be mounted tool-free, made of antistatic plastic
- Auto-stop carbon brushes to protect the motor
- Connection for dust extraction Ø 35/41 mm

**Technical data****Characteristics**

Cutting disc Ø	125 mm / 5 "
Max. cutting depth	27 mm / 1 1/16 "
Rated input power	1350 W
Output power	830 W
No-load speed	9600 rpm
Spindle thread	5/8" - 11 UNC
Weight (without power cable)	2.5 kg / 5.5 lbs
Cable length	2.5 m / 8 ft

**Vibration**

Vibration	5.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

**Noise emission**

Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

**Scope of delivery**

Guard  
Nut with two holes  
Metabo VibraTech (MVT) side handle  
Flat-pin spanners  
Inner support flange