

WEV 17-125 Quick Inox (600517420) Angle grinder (110-120 V / 50 - 60 Hz); Cardboard box; with speed control, quick-locking nut

Order no. 600517420
EAN 4061792176249



Product may differ from Image



- Perfect processing of stainless steel: robust, powerful angle grinder with high gear reduction and adjustable reduced speed for cool finish
- Longer service life, more power: the Metabo Longlife-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

Disc-Ø	125 mm // 5 "
Rated input power	1700 W
Output power	1040 W
No-load speed	2000 - 7600 rpm
Speed at rated load	7600 rpm
Torque	5 Nm / 44 in-lbs
Spindle thread	5/8" - 11 UNC
Handle circumference	206 mm / 8 1/8 "
Weight (without power cable)	2.5 kg / 5.5 lbs
Cable length	2.5 m / 8 ft

Vibration

Surface grinding	4.7 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Polishing	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Grinding with sandpaper	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Guard
 Metabo VibraTech (MVT) side handle
 Inner support flange
 M-Quick flange nut