

GE 710 Plus (600616380) Die grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600616380
EAN 4007430212382



Product may differ from Image



- Universal die grinder with long grinding spindle for deburring, milling, grinding and cutting, also in hard-to-reach places
- Spindle lock for simple change of tools
- Aluminium die-cast bearing flange for long service life of the machine
- Vario-Constamatic (VC)- Electronics for work with materials requiring customised speeds, which remain almost constant under load
- Thumbwheel for Speed Preselection
- Electronic safety shutdown of the motor for safe working in case the tool stops unexpectedly
- Restart protection: prevents unintentional start-up after power supply interruption
- Electronic overload protection for long service life
- Precise collar for stationary use
- Removable protective rubber cap for comfortable and safe working
- Slim design for ideal handling
- Precision collet for precise concentricity
- Metabo Marathon motor with patented dust protection for long service life

Technical data**Characteristics**

| | |
|------------------------------|-------------------|
| No-load speed | 10000 - 30500 rpm |
| Rated input power | 710 W |
| Output power | 430 W |
| Speed at rated load | 24000 rpm |
| Collar diameter | 43 mm / 1 11/16 " |
| Collet chuck bore | 6 mm / 0.2362 " |
| Weight (without power cable) | 1.6 kg / 3.5 lbs |
| Cable length | 4 m / 13 ft |

Vibration

| | |
|----------------------------------|-----------------------|
| Surface grinding (up to Ø 25 mm) | 5.6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Surface grinding (up to Ø 50 mm) | 16.9 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 80 dB(A) |
| Sound power level (LwA) | 91 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Collet 6 mm
Protective rubber cap
1 Open-jawed spanner