

UHEV 2860-2 Quick (600713500) Multi Hammer
(220-240 V / 50 - 60 Hz); Plastic Carry Case; with Metabo Quick change chuck

Order no. 600713500
EAN 4007430306234



Product may differ from image



- Multi hammer with 4 functions: hammer drilling, drilling without impact in two speeds and chiselling
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for drilling in wood and metal
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Thumbwheel for preselection of the speed and impact rate
- Two-speed gear unit: two drilling speeds for effective drilling in wood and metal
- Metabo Marathon-motor with dust protection for long service life
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Perfect ergonomics thanks to the centre of gravity being near the hand and optimised handle contour
- Bottom switch protected against damage and dust
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Restart protection: prevents unintentional start-up after power supply interruption
- Lockable switch for comfortable working in continuous operation
- Cable-protecting ball joint for optimal freedom of motion when working

Technical data

Characteristics

| | |
|-------------------------------------|--------------------------------|
| Max. single blow energy (EPTA) | 3.4 J |
| Maximum impact rate | 4500 bpm |
| Rated input power | 1100 W |
| Drill-Ø concrete with hammer drills | 28 mm / 1 3/32 " |
| Drill-Ø masonry with core bits | 68 mm / 2 11/16 " |
| Drill Ø steel | 13 / 6 mm // 1/2 / 1/4 " |
| Drill-Ø soft wood | 35 / 30 mm // 1 3/8 / 1 3/16 " |
| No-load speed | 0 - 900 / 0 - 2100 rpm |
| Revolutions at rated load | 900 / 2100 rpm |
| Bit retainer | SDS-plus |
| Collar diameter | 50 mm / 1 31/32 " |
| Weight (without power cable) | 3.3 kg / 7.4 lbs |
| Cable length | 4 m / 13 ft |

Vibration

| | |
|------------------------------|-----------------------|
| Drilling in metal | 4.3 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Hammer drilling concrete | 13.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 7.2 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 90 dB(A) |
| Sound power level (LWA) | 99 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Hammer chuck for tools with SDS-plus shank end
 Drilling depth guide
 Plastic carry case
 Keyless chuck for tools with cylindrical shank
 rubber-coated side handle