

KH 5-40 (600763620) Combination hammer (120 V / 60 Hz); Plastic Carry Case

Order no. 600763620
EAN 4007430331861



Product may differ from Image



- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life

Technical data

Characteristics

| | |
|-------------------------------------|-------------------|
| Max. single blow energy (EPTA) | 7.1 J |
| Maximum impact rate | 2800 bpm |
| Drill-Ø concrete with hammer drills | 40 mm / 1 9/16 " |
| Drill-Ø masonry with core bits | 105 mm / 4 1/8 " |
| No-load speed | 620 rpm |
| Bit retainer | SDS-max |
| Collar diameter | 61 mm / 2.4 " |
| Weight (without power cable) | 7.1 kg / 15.7 lbs |
| Cable length | 2.5 m / 8.2 ft |

Vibration

| | |
|------------------------------|-----------------------|
| Hammer drilling concrete | 16.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 13.3 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 95 dB(A) |
| Sound power level (LWA) | 106 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

- rubber-coated side handle
- Plastic carry case
- Drilling depth guide
- Lubricant for tool shank end