

KHA 36 LTX (600795840) Cordless combination hammer 36V; metaBOX 165 L; with Metabo Quick change chuck

Order no. 600795840 EAN 4007430320186



Product may differ from Image









- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Ergonomic housing shape for chiselling tasks without side handle
- Metabo Quick: quick change between SDS Plus hammer chuck and keyless chuck for many different applications
- Variospeed (V) Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- With metaBOX, the intelligent solution for transport and storage

www.metabo.com 1/2



| Technical data | |
|-------------------------------------|-----------------------|
| Characteristics | |
| Type of battery pack | Lipower |
| Battery voltage | 36 V |
| Max. single blow energy (EPTA) | 3.1 J |
| Maximum impact rate | 4500 bpm |
| Drill-Ø concrete with hammer drills | 32 mm / 1 1/4 " |
| Drill-Ø masonry with core bits | 68 mm / 2 11/16 " |
| Drill Ø steel | 13 mm / 1/2 " |
| Drill-Ø soft wood | 30 mm / 1 3/16 " |
| No-load speed | 0 - 1100 rpm |
| Bit retainer | SDS-plus |
| Weight without battery pack | 3.5 kg / 7.7 lbs |
| Weight with battery pack | 4.9 kg / 10.8 lbs |
| Vibration | |
| Hammer drilling concrete | 13 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 10.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 88 dB(A) |
| Sound power level (LwA) | 99 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Hammer chuck for tools with SDS-plus shank end Drilling depth guide metaBOX 165 L Keyless chuck for tools with cylindrical shank

Metabo VibraTech (MVT) side handle

www.metabo.com 2/2