

## HWA I 4500 Inox (600979180) Automatic domestic water system (220-240 V / 50 Hz); Cardboard box

Order no. 600979180  
EAN 4007430264060



Product may differ from Image



- Complete system in compact design with integrated filter and check valve integrated as standard for easy installation
- For automatic water supply, for garden irrigation and groundwater pumping as well as pumping, pumping empty, circulation of clear water
- Intelligent electronics for automatic appropriate and energy-saving modes
- Metabo pump protection: automatic dry-run protection with LED display to protect the pump and high user safety
- Integrated, washable filter protects the pump from contamination
- Integrated check valve prevents dry running of the pump when it is switched off, enabling a short restart process
- Maintenance-free capacitor motor
- Overload protection: protects the motor from overheating
- High-quality slip seal system for long service life
- Durable stainless steel pump housing
- Separate water filling opening for comfortable operation of the pump
- Water drain plug (removable without tools) for protection in case of frost
- Rubberised feet for low-noise and low-vibration operation
- For garden irrigation with 1 to 3 sprinklers

## Technical data

### Characteristics

|                             |                                                   |
|-----------------------------|---------------------------------------------------|
| Rated input power           | 1300 W                                            |
| Maximum delivery rate       | 4500 l/h / 1189 gal/h                             |
| Maximum delivery height     | 48 m / 157 ft                                     |
| Maximum pressure            | 4.8 bar / 70 psi                                  |
| Maximum suction height      | 8 m / 26 ft                                       |
| Switch-on pressure approx.  | 1.6 bar / 23.2 psi                                |
| Switch-off pressure approx. | 4.8 bar / 69.6 psi                                |
| Suction port                | 1" female thread                                  |
| Discharge port              | 1" female thread                                  |
| Pump housing                | Stainless steel                                   |
| Protection type IP          | IP X4                                             |
| Drive shaft                 | Stainless steel                                   |
| Number of impellers         | 1                                                 |
| Dimensions                  | 489 x 222 x 303 mm // 19 1/4 x 8 3/4 x 11 15/16 " |
| Weight                      | 11.5 kg / 25.4 lbs                                |
| Cable length                | 1.5 m / 5 ft                                      |

### Noise emission

|                              |            |
|------------------------------|------------|
| Sound pressure level         | 70 dB(A)   |
| Sound power level (LwA)      | 82.2 dB(A) |
| Uncertainty of measurement K | 2.8 dB(A)  |

## Scope of delivery

Fabric Sealing Tape  
Filter Key