

MT 400 Quick (601406000) Multi-tools (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 601406000 EAN 4007430316882



Product may differ from Image





- Indispensable for interior development such as cutting, sanding and scraping of different materials
- Tool holder for maximum compatibility to OIS, Starlock and other accessories
- Metabo Quick tool change system for time-saving, convenient change of accessories
- Fast and powerful thanks to the combination of a large oscillation angle of 3.2° and VTC-Electronics to maintain constant speed even under load
- Extra bright double LED lights for good visibility of the working area
- Slim design and non-slip soft-grip surface for optimised handling
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

www.metabo.com 1/2



Technical data	
Characteristics	
Orbital frequency with no load	11000 - 18500 rpm
Rated input power	400 W
Oscillation angle left/right	1.6 °
Bit retainer	Compatible with OIS and Starlock
Base plate, dimensions from corner to corner	93 mm / 3 5/8 "
Weight (without power cable)	1.4 kg / 3.2 lbs
Cable length	4 m / 15 3/4 "
Vibration	
Surface grinding	5 m/s ²
Uncertainty of measurement K	1.5 m/s²
Scraping	3.7 m/s²
Uncertainty of measurement K	1.5 m/s²
Sawing with plunge cut saw blade	6.1 m/s²
Uncertainty of measurement K	1.5 m/s²
Sawing with segmented sawing blade	4.6 m/s²
Uncertainty of measurement K	1.5 m/s²
Noise emission	
Sound pressure level	83 dB(A)
Sound power level (LwA)	94 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Plunge saw blade 32 mm HCS (wood)

Multi-adapter

Triangular hook and loop sanding plate 93 mm

Suction Adapter

www.metabo.com 2 / 2