# Basic 250-24 W OF (601532000) Compressor

**(220-240 V / 50 Hz); Cardboard box**

Order no. 601532000
EAN 4007430244413




Product may differ from Image




- Powerful, robust compressor for simple, commercial use
- Oil-free piston compressor: simple transportation and reduced service requirements
- For single phase alternating current
- Operating pressure can be regulated according to application by means of a pressure reducer and manometer
- Convenient pressure switch for good cold starting, complete with relief valve
- Overload protection: protects the motor from overheating
- Rubberised, stable wheels for mobile use
- Additional manometer for displaying the tank pressure
- Rubber-coated handle for comfortable handling
- 10 year tank warranty against rust

## Technical data

### Characteristics

| | |
|---|---|
| Suction rate | 220 l/min / 7.8 cfm |
| Filling capacity | 120 l/min / 4.2 cfm |
| Effective delivery volume (at 80% max. pressure) | 100 l/min / 3.5 cfm |
| Maximum pressure | 8 bar / 116 psi |
| Rated input power | 1.5 kW / 2 HP |
| Maximum speed | 2850 rpm |
| Tank capacity | 24 l / 6.3 gal |
| Sound pressure level (LpA) | 82 dB(A) |
| Sound power level (LwA) | 97 dB(A) |
| Dimensions | 620 x 340 x 580 mm // 24 13/32 x 13 3/8 x 22 27/32 " |
| Weight | 24 kg / 53 lbs |
| Cable length | 1.5 m / 5 ft |

### Noise emission

| | |
|---|---|
| Sound pressure level | 82 dB(A) |
| Sound power level (LwA) | 97 dB(A) |

## Scope of delivery

Universal quick-action coupling

Pull handle with rubber-grip