

SCV 18 LTX BL 1.6 (601615840) Cordless metal shears 18V; metaBOX 145

Order no. 601615840
EAN 4061792183339



Product may differ from Image



- Very handy and manoeuvrable cordless sheet-metal shears for burr-free cutting of sheet metal on site
- Maximum cornering ability, for comfortable cutting of narrow radii from 15 mm
- Faster working, thanks to the efficient brushless motor
- Infinitely adjustable cutting speed for individual customisation to the given material and task at hand
- Comfortable handling thanks to low weight, slim grip area and switch located on the top
- Blade spacing can be flexibly adjusted to different sheet thicknesses
- Economical four-way reversible blade, with the highest cut quality
- Maximum safety in every cutting direction, thanks to large hand guard
- Electronic overload protection for long service life
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| | |
|---|-------------------------|
| Type of battery pack | Li-Power |
| Battery voltage | 18 V |
| Max. sheet thickness for steel: 400 N/mm ² | 1.6 mm / 0.0629 " |
| Max. sheet thickness for steel: 600 N/mm ² | 1.2 mm / 0.0472 " |
| Max. sheet thickness for steel: 800 N/mm ² | 0.7 mm / 0.0275 " |
| Max. sheet thickness for aluminium: 250 N/mm ² | 2 mm / 0.0787 " |
| Strokes in idle | 1350 - 4840 rpm |
| Cutting speed | 7 m/min // 275 inch/min |
| Starting hole diameter | 27 mm / 1.0629 " |
| Smallest curve radius | 15 mm / 0.5905 " |
| Weight without battery pack | 1.4 kg / 3.1 lbs |
| Weight with battery pack | 1.8 kg / 4 lbs |

Vibration

| | |
|------------------------------|----------------------|
| Cutting of sheets | 7.6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 74 dB(A) |
| Sound power level (LwA) | 85 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

2 reversible blades
 metaBOX 145
 without battery pack, without charger
 Feeler gauge
 2 Hexagonal wrenches