

## WPB 18 LT BL 11-150 Quick (601737620) Cordless angle grinder 18V 2x5.5Ah LiHD; Charger ASC 145; metaBOX 165 L; with brake, quick-locking nut

Order no. 601737620 EAN 4061792228627



Product may differ from Image






















- Service-free Brushless motor with highest efficiency and maximum handiness
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated switch
- Fast brake system for highest user safety stops the disc within a matter of seconds after switching off
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Battery pack can be rotated in 90° steps for best ergonomics in any working position
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety
- Restart protection: prevents unintentional start-up after battery pack change
- Detachable dust protection filter protects motor from coarse particles
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

www.metabo.com 1/2



Technical data	
Characteristics	
Type of battery pack	LiHD
Battery pack capacity	2 x 5.5 Ah
Battery voltage	18 V
Disc-Ø	150 mm / 6 "
Max. cutting depth	46 mm / 1.811 "
No-load speed	10000 rpm
Spindle thread	5/8" - 11 UNC
Handle circumference	160 mm / 6.299 "
Weight without battery pack	1.8 kg / 3.97 lbs kg
Weight with battery pack	2.8 kg
Vibration	
Surface grinding	8.8 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s²
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s²
Noise emission	
Sound pressure level	81 dB(A)
Sound power level (LwA)	92 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Cutting guard clip 150 mm

M-Quick flange nut

Side handle

**Dust Protection Filter** 

2 LiHD battery packs (18 V/5.5 Ah)

Quick charger ASC 145 "AIR COOLED"

metaBOX 165 L

2 Guards (115 mm and 150 mm)

Inner support flange

www.metabo.com 2 / 2