

## PFM 17 (601789620) Metal weld bead remover (120 V / 60 Hz); metaBOX 280 L

Order no. 601789620 EAN 4061792210356



Product may differ from Image











- Fast, clean removal of weld beads in one work step with the newly developed metal weld bead remover
- Small metal chips are generated during face milling (no metal dust that is a health hazard)
- One-touch controller: Patented, tool-free setting of the cutting depth in 0.1mm steps.
- Ready for use in a matter of seconds thanks to fixable, magnetic guide rail (50 cm long, expandable).
- Simple, comfortable change of the indexable inserts at the milling head
- Slim handle area and large bow-type handle that can be adjusted without tools for safe, uniform guidance
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Electronic soft start and restart protection
- With metaBOX, the intelligent solution for transport and storage

www.metabo.com 1/2



Technical data	
Characteristics	
No-load speed	8000 - 12600 rpm
Rated input power	1700 W
Output power	970 W
Removal width	25 mm / 0.984 "
Removal height	- 1.5 - 10 mm // - 0.059 - 0.39 "
Grading of cutting depth setting	0.1 mm / 0.004 "
Weight (without power cable)	4.6 kg
Cable length	3.6 m
Vibration	
Vibration	4.1 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	91 dB(A)
Sound power level (LwA)	102 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Magnetic guide rail (50 cm long) Screwdriver for Torx screws 15

Screwdriver SW 4 with T-handle

Open-jawed spanner SW 10

metaBOX 280 L

3 Carbide indexable inserts Universal

Bow-type handle

www.metabo.com 2 / 2