

## **SB 18 Set (602245600) Cordless hammer drill**

**18V 2x2Ah Li-Power; Charger ASC 55 (110-120 V / 50 - 60 Hz); Plastic Carry Case; Mobile Workshop**

Order no. 602245600

EAN 4007430306630



Product may differ from Image



- Light, compact cordless hammer drill with extremely compact design for versatile use
- Hammer drill function for drilling in masonry
- Mobile workshop: plastic carry case with a wide range of accessories for drilling, screwdriving and more
- Integrated working light to illuminate the contact area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                               |
|-----------------------------|-------------------------------|
| Type of battery pack        | Li-Power                      |
| Battery voltage             | 18 V                          |
| Battery pack capacity       | 2 x 2 Ah                      |
| Maximum torque, soft        | 24 Nm / 212 in-lbs            |
| Maximum torque, hard        | 48 Nm / 425 in-lbs            |
| Adjustable torque           | 0.5 - 4.5 Nm // 4 - 40 in-lbs |
| Drill-Ø masonry             | 10 mm / 3/8 "                 |
| Drill Ø steel               | 10 mm / 3/8 "                 |
| Drill-Ø soft wood           | 20 mm / 3/4 "                 |
| No-load speed               | 0 - 450 / 0 - 1600 rpm        |
| Maximum impact rate         | 24000 bpm                     |
| Chuck capacity              | 1 - 10 mm // 1/32 - 3/8 "     |
| Weight without battery pack | 0.92 kg / 2 lbs               |
| Weight with battery pack    | 1.3 kg / 2.9 lbs              |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Drilling in metal            | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Impact drilling concrete     | 23 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 86 dB(A) |
| Sound power level (LwA)      | 97 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Keyless chuck  
 Charger ASC 55 "AIR COOLED"  
 Plastic carry case  
 Accessory set  
 Belt hook and bit case  
 2 Li-Power battery packs (18 V/2.0 Ah)