

## SB 18 LTX BL I (602360650) Cordless hammer drill 18V 2x5.2Ah Li-Power; Charger ASC 55 (220-240 V / 50 - 60 Hz); metaBOX 145 L

Order no. 602360650 EAN 4061792187863



Product may differ from Image













- Brushless hammer drill with maximum power for demanding applications
- Hammer drill function for drilling in masonry
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

www.metabo.com 1/2



| Technical data               |                             |
|------------------------------|-----------------------------|
| Characteristics              |                             |
| Type of battery pack         | Li-Power                    |
| Battery voltage              | 18 V                        |
| Battery pack capacity        | 2 x 5.2 Ah                  |
| Maximum torque, soft         | 65 Nm / 575 in-lbs          |
| Pulse torque                 | 65 Nm / 575 in-lbs          |
| Maximum torque, hard         | 130 Nm / 1151 in-lbs        |
| Adjustable torque            | 1 - 20 Nm // 9 - 177 in-lbs |
| Drill-Ø masonry              | 16 mm / 5/8 "               |
| Drill Ø steel                | 13 mm / 1/2 "               |
| Drill-Ø soft wood            | 68 mm / 2.68 "              |
| No-load speed                | 0 - 550 / 0 - 2000 rpm      |
| Maximum impact rate          | 38000 bpm                   |
| Chuck capacity               | 1.5 - 13 mm // 1/16 - 1/2 " |
| Collar diameter              | 43 mm / 1 11/16 "           |
| Weight without battery pack  | 1.8 / 4                     |
| Weight with battery pack     | 2.5 kg / 5.5 lbs            |
| Vibration                    |                             |
| Drilling in metal            | 2.6 m/s <sup>2</sup>        |
| Uncertainty of measurement K | 1.5 m/s²                    |
| Impact drilling concrete     | 16.5 m/s²                   |
| Uncertainty of measurement K | 1.7 m/s²                    |
| Noise emission               |                             |
| Sound pressure level         | 92 dB(A)                    |
| Sound power level (LwA)      | 103 dB(A)                   |
| Uncertainty of measurement K | 3 dB(A)                     |

## Scope of delivery

Keyless chuck

2 Li-Power battery packs (18 V/5.2 Ah)

Charger ASC 55 "AIR COOLED"

metaBOX 145 L

Side handle

Belt hook and bit case

www.metabo.com 2/2