

SB 18 LTX BL Q I (602361660) Cordless hammer drill

18V 2x5.5Ah LiHD; Charger ASC 145 (220-240 V / 50 - 60 Hz); metaBOX 145 L

Order no. 602361660
EAN 4061792187832



Product may differ from Image



- Brushless hammer drill with maximum power for demanding applications
- Hammer drill function for drilling in masonry
- Metabo Quick System: quick change of bit retainer and bits, for flexible working
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- Overload protection: protects the motor from overheating
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| | |
|-----------------------------|-----------------------------|
| Type of battery pack | LiHD |
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 5.5 Ah |
| Maximum torque, soft | 65 Nm / 575 in-lbs |
| Pulse torque | 65 Nm / 575 in-lbs |
| Maximum torque, hard | 130 Nm / 1151 in-lbs |
| Adjustable torque | 1 - 20 Nm // 9 - 177 in-lbs |
| Drill-Ø masonry | 16 mm / 5/8 " |
| Drill Ø steel | 13 mm / 1/2 " |
| Drill-Ø soft wood | 68 mm / 2.68 " |
| No-load speed | 0 - 550 / 0 - 2000 rpm |
| Maximum impact rate | 38000 bpm |
| Chuck capacity | 1.5 - 13 mm // 1/16 - 1/2 " |
| Collar diameter | 43 mm / 1 11/16 " |
| Weight without battery pack | 1.8 kg / 4 lbs |
| Weight with battery pack | 2.8 kg / 6.2 lbs |

Vibration

| | |
|------------------------------|-----------------------|
| Drilling in metal | 2.6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Impact drilling concrete | 16.5 m/s ² |
| Uncertainty of measurement K | 1.7 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 92 dB(A) |
| Sound power level (LWA) | 103 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Quick-change chuck
 2 LiHD battery packs (18 V/5.5 Ah)
 Quick charger ASC 145 "AIR COOLED"
 metaBOX 145 L
 Side handle
 Belt hook and bit case