

SP 28-50 S Inox (604114180) Construction and dirty water pump (220-240 V / 50 Hz); Cardboard box

Order no. 604114180
EAN 4007430263643



Product may differ from Image



- For drainage and pumping dry of construction pits, cellars and shafts. Also for pumping sewage and waste water in industrial and domestic environments.
- For very coarse dirty water with solid bodies of up to Ø 50 mm
- Double mechanical seal with oil chamber for ideal protection of the pump if the water is very dirty
- Self-cleaning Vortex-impeller to minimise blockages
- Designed for continuous mode with S1 motor operating mode
- Overload protection: protects the motor from overheating
- Float switch for automatic mode
- Suitable for mobile and stationary use thanks to ergonomic handles and stability
- Durable pump housing made of non-corrosive, high-quality stainless steel

Technical data**Characteristics**

Rated input power	1470 W
Maximum delivery rate	28000 l/h / 7397 gal/h
Maximum delivery height	12 m / 39 ft
Maximum pressure	1.2 bar / 17.4 psi
Maximum immersion depth	7 m / 23 ft
Discharge port	2" female thread
Pump housing	Stainless steel
Protection type IP	IP 68
Maximum particle size up to	50 mm / 2 "
Number of impellers	1
Dimensions	203 x 170 x 537 mm // 8 x 6 11/16 x 21 1/8 "
Weight	19.3 kg / 42.5 lbs
Cable length	10 m / 33 ft

Scope of delivery

Float switch