

KHE 2644 (606157380) Combination Hammer
(220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 606157380
EAN 4007430292674



Product may differ from Image



- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Electronic soft start for precise spot-drilling
- High performance hammer action, precisely mounted in a housing made of aluminium alloy: long-lasting and robust
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Lockable switch for comfortable working in continuous operation

Technical data

Characteristics

Max. single blow energy (EPTA)	2.3 J
Maximum impact rate	5400 bpm
Rated input power	800 W
Drill-Ø concrete with hammer drills	26 mm / 1 "
Drill-Ø masonry with core bits	68 mm / 2 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	30 mm / 1 3/16 "
No-load speed	0 - 1150 rpm
Revolutions at rated load	960 rpm
Bit retainer	SDS-plus
Collar diameter	43 mm / 1 11/16 "
Weight (without power cable)	2.9 kg / 6.4 lbs
Cable length	4 m / 159 7/16 "

Vibration

Hammer drilling concrete	13.7 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Chiseling	15 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	87 dB(A)
Sound power level (LWA)	98 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Hammer chuck for tools with SDS-plus shank end
 Plastic carry case
 Side handle
 Drilling depth guide