

W 22-180 MVT (606461190) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box; with rotating main handle

Order no. 606461190
EAN 4007430268372



Product may differ from Image



- Metabo Marathon motor with patented dust protection for long service life
- Deadman's switch for high user protection
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

| | |
|------------------------------|-------------------|
| Disc-Ø | 180 mm // 7 " |
| Rated input power | 2200 W |
| Output power | 1500 W |
| No-load speed | 8450 rpm |
| Speed at rated load | 5800 rpm |
| Torque | 11 Nm / 97 in-lbs |
| Spindle thread | M 14 |
| Handle circumference | 144 mm / 5.669 " |
| Weight (without power cable) | 5.7 kg / 12.6 lbs |
| Cable length | 4 m / 13 ft |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 6.1 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 94 dB(A) |
| Sound power level (LwA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard
 Metabo VibraTech (MVT) side handle
 Flat-pin spanner
 Inner support flange
 Nut with two holes