

W 24-230 MVT (606467420) Angle grinder (110-120 V / AC/DC 0/50/60 Hz); Cardboard box; with rotating main handle

Order no. 606467420 EAN 4007430268181



Product may differ from Image

- Metabo Long-life motor with patented dust protection for long service life
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

| Disc-Ø | 230 mm // 9 " |
|------------------------------|----------------------|
| | |
| No-load speed | 6600 rpm |
| Speed at rated load | 4600 rpm |
| Torque | 17 Nm / 150 in-lbs |
| Spindle thread | 5/8" - 11 UNC |
| Handle circumference | 144 mm / 5.669 " |
| Weight (without power cable) | 5.8 kg / 12.8 lbs |
| Cable length | 4 m / 13 ft |
| Vibration | |
| Surface grinding | 6.2 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 94 dB(A) |
| Sound power level (LwA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |
| | |

Scope of delivery

Guard

Metabo VibraTech (MVT) side handle