

WE 24-180 MVT (606468000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box; with rotating main handle

Order no. 606468000 EAN 4007430268105



Product may differ from Image



- Metabo Marathon motor with patented dust protection for long service life
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic overload protection and restart protection
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor
- LED signal indicates triggered restart protection or overheating

Technical data

Characteristics

| Disc-Ø | 180 mm // 7 " |
|---|-----------------------|
| Rated input power | 2400 W |
| Output power | 1600 W |
| No-load speed | 8450 rpm |
| Speed at rated load | 5800 rpm |
| Torque | 14 Nm / 124 in-lbs |
| Spindle thread | M 14 |
| Handle circumference | 144 mm / 5.669 " |
| Weight (without power cable) | 5.7 kg / 12.6 lbs |
| Cable length | 4 m / 13 ft |
| Vibration | |
| Surface grinding | 6.1 m/s² |
| Uncertainty of measurement K | 1.5 m/s² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s² |
| Noise emission | |
| | |
| Sound pressure level | 94 dB(A) |
| Sound pressure level Sound power level (LwA) | 94 dB(A) 105 dB(A) |

Scope of delivery

Guard Metabo VibraTech (MVT) side handle Flat-pin spanner Inner support flange Nut with two holes