

## W 26-230 MVT (606474420) Angle grinder (110-120 V / AC/DC 0/50/60 Hz); Cardboard box; with rotating main handle

Order no. 606474420 EAN 4007430268310



Product may differ from Image







- Metabo Long-life motor with patented dust protection for long service life
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Tool-free adjustable guard; twist-proof
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data	
Characteristics	
Disc-Ø	230 mm // 9 "
No-load speed	6600 rpm
Speed at rated load	4800 rpm
Torque	18 Nm / 160 in-lbs
Spindle thread	5/8" - 11 UNC
Handle circumference	144 mm / 5.669 "
Weight (without power cable)	6.3 kg / 13.9 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	6.4 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

www.metabo.com 2/2