

WQ 1100-125 (610035190) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box; with quick-locking nut

Order no. 610035190 EAN 4007430338518



Product may differ from Image





- Robust, universal and economical: powerful angle grinder for any application
- Powerful motor with good overload capacity
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting

www.metabo.com 1/2



| Technical data | |
|------------------------------|----------------------|
| Characteristics | |
| Disc-Ø | 125 mm // 4.9 " |
| Rated input power | 1100 W |
| Output power | 700 W |
| No-load speed | 12000 rpm |
| Speed at rated load | 7000 rpm |
| Torque | 3.5 Nm / 31 in-lbs |
| Spindle thread | M 14 |
| Handle circumference | 194 mm / 7 5/8 " |
| Weight (without power cable) | 2.2 kg / 4.9 lbs |
| Cable length | 4 m / 13 ft |
| Vibration | |
| Surface grinding | 7.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 87 dB(A) |
| Sound power level (LwA) | 98 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard

Side handle

Inner support flange

M-Quick flange nut

www.metabo.com 2 / 2