

TS 254 M (610254190) Table saw

Cardboard box

Order no. 610254190
EAN 4061792180321



Product may differ from Image



- Compact mobile table saw with impressive cutting performance and high comfort for working
- Anti-twist tubular frame construction for highest demands on the building site and during installations
- Cables and all add-on components for transport can be stored on the casing
- Powerful motor with electronic overload protection
- Motor brake for quick stop of the saw blade in 3 seconds
- Restart protection: prevents unintentional start-up after power supply interruption
- Soft start for long service life of motor and drive
- Precisely adjustable parallel guide / rip fence with double clamping and quick fastening
- Precise saw blade inclination via gear guide
- Automatic resetting to 0 – 45 ° after undercuts
- Easy saw blade change with spindle lock
- Splitting wedge can be lowered without tools for hidden cuts and transport
- Precise, extendable table width extension for extra large working surfaces

Technical data

Characteristics

| | |
|---------------------------------------|--|
| Dimensions | 669 x 748 x 334 mm // 26.343 x 29.437 x 13.156 " |
| Working height | 334 mm // 13.15 " |
| Cutting height | 0 - 80 mm // 0 - 3.15 " |
| Maximum cutting height 90/45° | 80 / 48 mm // 3.15 / 1.87 " |
| Maximum cutting width at rip fence | 520 mm / 20.46 " |
| Maximum material width at mitre fence | 195 mm / 7.68 " |
| No-load speed | 4200 rpm |
| Cutting speed | 56 m/s / 184 ft/s |
| Saw blade | 254 x 30 mm // 10 x 1.181 " |
| Saw blade swivel range | -1.5 - 46.5 ° |
| Rated input power S1 100% | 1500 W |
| Weight | 24.4 kg / 54 lbs |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 92 dB(A) |
| Sound power level (LwA) | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Carbide saw blade with alternately bevel-ground tips (40 teeth)

Table Length Extension

Table width extension (right)

Push stick

Rip Fence

Mitre Fence