

WB 18 LTX BL 125 Quick Set (613077930) Cordless Angle Grinders 3x18V LiHD; Charger ASC 30-36 V (220-240 V / 50 - 60 Hz); MetaLoc

Order no. 613077930
EAN 4007430318510



Product may differ from Image



- Unique encapsulated Metabo brushless motor with optimum protection from dust provides quick work progress and the highest efficiency
- Slim design for prolonged comfort when working overhead or in areas with limited space
- Fast brake system for highest user safety stops the disc within a matter of seconds after switching off
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Battery pack can be swivelled for better access in hard to reach places
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Detachable dust protection filter protects motor from coarse particles
- LiHD battery pack for ultimate performance, extremely long runtime and service life
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.
- Battery packs with capacity display for checking the charge status

Technical data

Characteristics

| | |
|---------------------------------|------------------|
| Type of battery pack | LiHD |
| Battery pack voltage | 18 V |
| Grinding wheel Ø | 125 mm / 5 " |
| No-load speed | 9000 rpm |
| Spindle thread | M 14 |
| Weight (including battery pack) | 2.6 kg / 5.7 lbs |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 5 m/s ² |
| Uncertainty of measurement K | 2.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 82 dB(A) |
| Sound power level (LwA) | 93 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard
Side handle
Dust protection filter
LiHD battery pack (18 V/3.5 Ah)
2 LiHD battery packs (18 V/5.5 Ah)
Charger ASC 30-36 V "AIR COOLED"
MetaLoc case
Inner support flange
Quick-locking nut