

WEVF 10-125 Quick Inox (613080000) Flat-head angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 613080000
EAN 4007430275677



Product may differ from Image



- The most easy-to-handle flat-head angle grinder with speed regulation for perfect processing of stainless steel e.g. railings and hand rails
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Thumbwheel controlled Vario-Constamatic (VC)-Full wave electronics ideal for working on materials requiring customised speeds, and at speeds which remain almost constant under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

| | |
|------------------------------|--------------------|
| Minimum accessible angle | 43 ° |
| Disc-Ø | 125 mm / 5 " |
| Rated input power | 1000 W |
| Output power | 590 W |
| No-load speed | 2000 - 7600 rpm |
| Speed at rated load | 6300 rpm |
| Torque | 3.5 Nm / 31 in-lbs |
| Spindle thread | M 14 |
| Weight (without power cable) | 2.3 kg / 5.1 lbs |
| Cable length | 4 m / 13 ft |
| Handle circumference | 193 mm / 7.594 " |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 4.4 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 91 dB(A) |
| Sound power level (LwA) | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard
 Side handle
 1 Flap disc Flexiamant Super Convex (125mm; P60)
 Inner support flange
 Quick-locking nut