

TKHS 315 C - 2,8 DNB (0103152100) Table saw
(380-415 V / 50 Hz); Cardboard box; for three phase current

Order no. 0103152100

EAN 4003665404417



Product may differ from Image



- Restart protection: prevents unintentional start-up after power supply interruption
- Universal table saw with basic equipment
- Ideal for sawing squared timber, boards, panels and wood-like materials in the workshop and at construction sites
- Quiet induction motor with motor brake and overload protection - maintenance-free and robust.
- Universal guide with magnetic guide for precise straight cuts and mitre cuts
- Freely height-adjustable saw blade
- Comfortable setting of the saw blade inclination from the front
- Sturdy, powder-coated sheet steel design and galvanised table-top
- Foldable table length extension
- Frame and motor pre-mounted
- High torque three-phase motor

Technical data

Characteristics

| | |
|---------------------------------------|--|
| Dimensions | 1650 x 650 x 1000 mm // 5.5 x 2.2 x 3.3 ft |
| Max. support surface | 800 x 550 mm // 31 1/2 x 21 5/8 " |
| Working height | 850 mm // 33 1/2 " |
| Cutting height | 0 - 85 mm // 0 - 3 5/16 " |
| Maximum cutting height 90/45° | 85 / 60 mm // 3 5/16 / 2 3/8 " |
| Maximum cutting width at rip fence | 290 mm / 11 3/8 " |
| Maximum material width at mitre fence | 220 mm / 8 5/8 " |
| No-load speed | 2990 rpm |
| Cutting speed | 50 m/s / 164 ft/s |
| Saw blade | 315 x 30 mm // 12 3/8 x 1.181 " |
| Saw blade swivel range | 0 - 45 ° |
| Mains voltage | 380 - 415 V |
| Rated input power | 2800 W |
| Weight | 64 kg / 141 lbs |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 98 dB(A) |
| Sound power level (LWA) | 112 dB(A) |
| Uncertainty of measurement K | 4 dB(A) |

Scope of delivery

Carbide saw blade with alternately bevel-ground tips (24 teeth)
 Table extension (550 x 800 mm)
 Chip and Dust Extraction Unit
 Push stick
 Wheel set incl. handles
 Universal guide