

SXE 450 TurboTec (600129190) Random orbital sander
(220-240 V / 50 Hz); Cardboard box

Order no. 600129190
 EAN 4007430165541



Product may differ from Image

- Patented adjustable "Duo" oscillating circuit setting: Can be set depending on the application for fine sanding or high stock removal
- Variospeed (V) Electronics for working at customised speeds to suit various application materials
- Thumbwheel for speed preselection
- Turbo boost: allows additional power reserves to be employed for maximum removal
- Power Control System: No scratches when placing the machine directly onto the material at speed
- Grip area with non-slip soft-grip surface
- Removable side handle
- Dust-proof ball bearings for long service life of the machine
- Sturdy aluminium die cast bearing housing
- Easy to empty textile dust bag for working without extraction facilities
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- Multi-hole sanding pad for effective extraction and a longer service life of the sanding medium

Technical data**Characteristics**

| | |
|--------------------------------|----------------------------|
| Diameter of backing pad | 150 mm / 6 " |
| Rated input power | 350 W |
| No-load speed | 4200 - 11000 rpm |
| Orbital frequency with no load | 8400 - 22000 opm |
| Orbit diameter | 2.8 / 6.2 mm / 1/8 / 1/4 " |
| Weight (without power cable) | 2.2 kg / 5.3 lbs |
| Cable length | 4 m / 13 ft |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 7 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 82 dB(A) |
| Sound power level (LwA) | 93 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Sanding pad "multi-hole" with hook and loop
Textile dust bags
Hexagonal wrench
removable side handle