

## LSV 5-225 Comfort (600136180) Long-neck sander (220-240 V / 50 - 60 Hz); Plastic Carry Case; with Variable Length Adjustment

Order no. 600136180  
EAN 4007430286000



Product may differ from Image



- For convenient sanding of primed surfaces on walls or ceilings
- Optional LED side light to help detect imperfections and serrations
- Optimum balance when working, as the centre of gravity of the machine is not at the sanding head
- Variable length adjustment: can be shortened or extended without tools for narrow rooms or high ceiling rooms
- Extendable to a total length of 2.1 m with additional extension (accessory)
- M-Clean technology: Effective extraction through the machine housing for maximum flexibility of the sanding head
- Ideal adaptation of the flexible sanding head to the surface for good work results
- Optimum extraction results thanks to spring-mounted brush rim that adapts to the surface.
- Vario-Constamatic (VC)-Full wave electronics for working at customised speeds to suit the application materials, and speeds that remain almost constant even under load
- Ergonomically shaped aluminium handle bar and T-handle for comfortable use in different positions
- Simple, quick and tool-free exchangeable shaft can be adjusted directly on site if needed
- Putting the machine down without kinking the hose and cable
- With extensive range of grinding media for every application
- Extraction possibility by means of connecting an all-purpose vacuum cleaner

## Technical data

### Characteristics

|                              |   |
|------------------------------|---|
| Sanding disc diameter        | 225 mm / 8 7/8 "                                  |
| No-load speed                | 1000 - 1650 rpm                                   |
| Rated input power            | 500 W   |
| Output power                 | 270 W   |
| Adjustable machine length    | 1.1 / 1.6 / 2.1 m // 41 3/8 / 61 7/32 / 81 1/16 " |
| Weight (without power cable) | 4.5 kg / 9.9 lbs                                  |
| Cable length                 | 4 m / 157 1/2 "                                   |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 76 dB(A) |
| Sound power level (LwA)      | 87 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Sanding pad (very soft)  
 Coupling bush  
 Extension  
 Hexagonal wrench  
 Plastic carry case  
 Hook and loop sanding sheets with multi-perforation (1 each of P80, P100, P120, P150)  
 Flexible shaft (as replacement)