

## KNS 18 LTX 150 (600191850) Cordless fillet weld grinder 18V; Cardboard box

Order no. 600191850  
EAN 4007430206770



Product may differ from Image



- Very flat cordless fillet weld grinder for processing stainless steel weld seams in tight spaces
- Robust motor for long service life
- Adjustable without tools, removable guard
- Low-maintenance belt drive for long service life
- Battery pack can be swivelled for better working in hard to reach places
- Detachable dust filter protects motor from coarse particles
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery pack change
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                  |
|-----------------------------|------------------|
| Type of battery pack        | Li-Power         |
| Battery voltage             | 18 V             |
| No-load speed               | 3800 rpm         |
| Disc diameter               | 150 mm / 6 "     |
| Spindle thread              | M 14             |
| Weight without battery pack | 2.4 kg / 5.3 lbs |
| Weight with battery pack    | 3.1 kg / 6.8 lbs |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Polishing                    | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 80 dB(A) |
| Sound power level (LwA)      | 91 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Guard  
Side handle  
Dust Protection Filter  
Flat-pin spanner  
Hexagonal wrench  
without battery pack, without charger  
Inner support flange  
Nut with two holes