

## W 9-100 (600350190) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600350190 EAN 4007430244499





Product may differ from Image

- Low fatigue as never before: compact angle grinder with smallest handle circumference in its class for perfect ergonomics
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

## Characteristics

| Disc-Ø                                       | 100 mm // 4 "         |
|--|-----------------------|
| Rated input power                            | 900 W                 |
| Output power                                 | 550 W                 |
| No-load speed                                | 10500 rpm             |
| Speed at rated load                          | 7500 rpm              |
| Torque                                       | 2.5 Nm / 22 in-lbs    |
| Spindle thread                               | M 10                  |
| Handle circumference                         | 193 mm / 7.5594 "     |
| Weight (without power cable)                 | 2 kg / 4.4 lbs        |
| Cable length                                 | 2.5 m / 8 ft          |
| Vibration                                    |                       |
| Surface grinding                             | 4.5 m/s <sup>2</sup>  |
| Uncertainty of measurement K                 | 1.5 m/s²              |
| Grinding with sandpaper                      | 2.5 m/s <sup>2</sup>  |
| Uncertainty of measurement K                 | 1.5 m/s <sup>2</sup>  |
| Noise emission                               |                       |
|  |                       |
| Sound pressure level                         | 93 dB(A)              |
| Sound pressure level Sound power level (LwA) | 93 dB(A)<br>104 dB(A) |

## Scope of delivery

Guard Side handle Flat-pin spanners Inner support flange Nut with two holes