

## W 9-115 (600354380) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600354380 EAN 4007430244604





Product may differ from Image

- Low fatigue as never before: compact angle grinder with smallest handle circumference in its class for perfect ergonomics
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Restart protection after power interruption
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

## Characteristics

| Disc-Ø  | 115 mm // 4 1/2 "                            |
|---|--|
| Rated input power                                       | 900 W  |
| Output power  | 550 W  |
| No-load speed   | 10500 rpm                                    |
| Speed at rated load                                     | 7500 rpm                                     |
| Torque  | 2.5 Nm / 22 in-lbs                           |
| Spindle thread  | M 14   |
| Handle circumference                                    | 193 mm / 7.5594 "                            |
| Weight (without power cable)                            | 2.1 kg / 4.6 lbs                             |
| Cable length  | 2.5 m / 8 ft                                 |
| Vibration   |  |
| Surface grinding  | 4.9 m/s <sup>2</sup>                         |
| Uncertainty of measurement K                            | 1.5 m/s <sup>2</sup>                         |
|   |  |
| Grinding with sandpaper                                 | 2.5 m/s <sup>2</sup>                         |
| Grinding with sandpaper<br>Uncertainty of measurement K | 2.5 m/s <sup>2</sup><br>1.5 m/s <sup>2</sup> |
|   |  |
| Uncertainty of measurement K                            |  |
| Uncertainty of measurement K Noise emission             | 1.5 m/s²                                     |

## Scope of delivery

Guard Side handle Flat-pin spanners Inner support flange Nut with two holes