

## W 9-115 Quick (600371190) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600371190  
EAN 4007430333933



Product may differ from Image



- Low fatigue as never before: compact angle grinder with smallest handle circumference in its class for perfect ergonomics
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

### Characteristics

|                              |                    |
|------------------------------|--------------------|
| Disc-Ø                       | 115 mm // 4 1/2 "  |
| Rated input power            | 900 W              |
| Output power                 | 550 W              |
| No-load speed                | 10500 rpm          |
| Speed at rated load          | 7500 rpm           |
| Torque                       | 2.5 Nm / 22 in-lbs |
| Spindle thread               | M 14               |
| Handle circumference         | 193 mm / 7.5594 "  |
| Weight (without power cable) | 2.1 kg / 4.6 lbs   |
| Cable length                 | 4 m / 13 ft        |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 4.9 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 93 dB(A)  |
| Sound power level (LwA)      | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Guard  
Side handle  
Inner support flange  
M-Quick flange nut