

BE 600/13-2 (600383000) Drill **(220-240 V / 50 - 60 Hz); Cardboard box**

Order no. 600383000

EAN 4007430261991



Product may differ from Image

- Handy drill especially for demanding metal processing
- Two-speed gearbox with wide speed range for versatile drilling work up to Ø 13 mm in steel
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Particularly compact design with small width across corners
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Thumbwheel for speed preselection
- Forward and reverse rotation
- Keyless chuck and spindle stop for convenient one-handed tool change
- Futuro top keyless chuck: automatic retightening when drilling for precise drilling results
- Handle with non-slip soft-grip surface

Technical data

Characteristics

Rated input power	600 W
Output power	290 W
Drill Ø steel	13 / 8 mm // 1/2 / 5/16 "
Drill-Ø soft wood	37 / 27 mm // 1 1/2 / 1 1/8 "
No-load speed	0 - 750 / 0 - 2500 rpm
Speed at rated load	450 / 1500 rpm
Gears	2
Maximum torque	31 / 9 Nm // 274 / 80 in-lbs
Collar diameter	43 mm / 1 11/16 "
Chuck capacity	1 - 13 mm // 1/32 - 1/2 "
Drill spindle with hexagonal recess	6.35 mm / 1/4 "
Drill spindle thread	1/2 " - 20 UNF
Weight (without power cable)	1.9 kg / 4.2 lbs
Cable length	4 m / 13 ft

Vibration

Drilling in metal	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	82 dB(A)
Sound power level (LwA)	93 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Futuro Top keyless chuck
 Side handle
 Open-jawed spanner