

## KHE 5-40 (600391500) Combination hammer (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 600391500  
EAN 4061792199255



Product may differ from Image



- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Easily accessible locking switch for chiselling in continuous mode
- Vario-Constamatic (VC)-Full wave electronics for working at customised speeds to suit the application materials, and speeds that remain almost constant even under load
- Thumbwheel for preselection of the speed and impact rate
- Electronic soft start for precise spot-drilling
- Optimum heat dissipation and low weight thanks to die cast magnesium gear housing
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Restart protection: prevents unintentional start-up after power supply interruption
- Low-dust chiselling and drilling with external dust extraction ESA max (accessories)
- Wear Indication for Carbon Brush
- Service display, e.g. to indicate when the carbon brush needs to be replaced, and an LED indicating mains voltage
- Early warning system thanks to service LED for targeted planning of the carbon brush replacement 8 working hours before switching off

## Technical data

### Characteristics

|                                     |                  |
|-------------------------------------|------------------|
| Max. single blow energy (EPTA)      | 8.5 J            |
| Maximum impact rate                 | 3000 bpm         |
| Rated input power                   | 1100 W           |
| Drill-Ø concrete with hammer drills | 40 mm / 1 9/16 " |
| No-load speed                       | 350 - 540 rpm    |
| Speed at rated load                 | 540 rpm          |
| Bit retainer                        | SDS-max          |
| Collar diameter                     | 61 mm / 2.4 "    |
| Weight (without power cable)        | 7.1              |
| Cable length                        | 6 m / 19.7 ft    |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Hammer drilling concrete     | 14.6 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Chiseling                    | 9.7 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 95 dB(A)  |
| Sound power level (LwA)      | 106 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Side handle  
Duster  
Plastic carry case  
Drilling depth guide  
Lubricant for tool shank end