

WE 15-150 Quick (600464420) Angle grinder (110-120 V / 60 Hz); Cardboard box

Order no. 600464420 EAN 4007430245533



Product may differ from Image















- Highest service life for extreme applications: robust, powerful angle grinder with maximum power density in its class for quick work progress
- Longer service life, more power: the Metabo Longlife-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data		
Characteristics		
Disc-Ø	150 mm // 6 "	
Output power	900 W	
No-load speed	9600 rpm	
Speed at rated load	9600 rpm	
Torque	3.9 Nm / 35 in-lbs	
Spindle thread	5/8" - 11 UNC	
Handle circumference	206 mm / 8 1/8 "	
Weight (without power cable)	2.6 kg / 5.7 lbs	
Cable length	2.5 m / 8 ft	
Vibration		
Surface grinding	6.8 m/s²	
Uncertainty of measurement K	1.5 m/s²	
Grinding with sandpaper	3.4 m/s²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Sound pressure level	93 dB(A)	
Sound power level (LwA)	104 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Guard

M-Quick flange nut

Metabo VibraTech (MVT) side handle

Clip for cut-off guard

Inner support flange

www.metabo.com 2 / 2