

WEP 17-125 Quick (600547000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600547000
EAN 4061792176263



Product may differ from Image



- Maximum productivity: 1,700 Watt angle grinder with the power of a large grinder and the compactness of a small one for quickest material removal on industrial applications
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated switch
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical data

Characteristics

| | |
|------------------------------|--------------------|
| Disc-Ø | 125 mm // 5 " |
| Rated input power | 1700 W |
| Output power | 1040 W |
| No-load speed | 11000 rpm |
| Speed at rated load | 11000 rpm |
| Torque | 3.7 Nm / 33 in-lbs |
| Spindle thread | M 14 |
| Handle circumference | 197 mm / 7 3/4 " |
| Weight (without power cable) | 2.5 kg / 5.5 lbs |
| Cable length | 4 m / 13 ft |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 3.6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 93 dB(A) |
| Sound power level (LwA) | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard
Metabo VibraTech (MVT) side handle
Inner support flange
M-Quick flange nut