

SBE 650 (600742530) Impact drill Plastic Carry Case

Order no. 600742530 EAN 4061792201439



Product may differ from Image

- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Thumbwheel for Speed Preselection
- Forward and reverse rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck

Technical data

Characteristics

| Rated input power | 650 W |
|-------------------------------------|-----------------------------|
| Output power | 320 W |
| Maximum torque | 10 Nm // 88 in-lbs |
| Drill-Ø masonry | 16 mm / 5/8 " |
| Drill-Ø concrete | 14 mm / 9/16 " |
| Drill Ø steel | 13 mm // 1/2 " |
| Drill-Ø soft wood | 30 mm // 1 3/16 " |
| Speed at rated load | 1500 rpm |
| Maximum impact rate | 44800 bpm |
| Gears | 1 |
| Chuck capacity | 1.5 - 13 mm // 1/16 - 1/2 " |
| Collar diameter | 43 mm / 1 11/16 " |
| Drill spindle with hexagonal recess | 6.35 mm / 1/4 " |
| Drill spindle thread | 1/2 " - 20 UNF |
| Chuck clamping type | Keyless chuck |
| Weight (without power cable) | 1.8 |
| Cable length | 2.5 m / 8 ft |
| Vibration | |
| Drilling in metal | 5.8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Impact drilling concrete | 24.4 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 91 dB(A) |
| Sound power level (LwA) | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Futuro Plus keyless chuck Plastic carry case Side handle Drilling depth guide