

## MHEV 11 BL (600770520) Chipping hammer (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 600770520  
EAN 4061792002739



Product may differ from Image



- High breaking performance thanks to maintenance-free brushless motor and high-performance hammer action
- Long service life thanks to brushless technology and robust aluminium die-cast housings of gear and motor
- Metabo VibraTech (MVT) with double dampening: Decoupled handle and impact-absorbing counter-oscillating weight actively reduce vibrations for healthy working also in continuous use.
- Ergonomically shaped, slim gripping area with large speed control trigger for comfortable working
- Easily accessible locking switch for chiselling in continuous mode
- Optional reduction of the impact energy for working in softer materials
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after power supply interruption
- Overload protection: protects the motor from overheating
- Low-dust chiselling with external dust extraction ESA max (accessories)
- The adjustable front handle can be rotated 360° and the angle adjusted for an optimum working position

## Technical data

### Characteristics

|                                |                     |
|--------------------------------|---------------------|
| Max. single blow energy (EPTA) | 18 J                |
| Maximum impact rate            | 2100 bpm            |
| Rated input power              | 1500 W              |
| Bit retainer                   | SDS-max             |
| Weight (without power cable)   | 12.2 kg / 27 lbs kg |
| Cable length                   | 6 m / 236 7/32 "    |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Chiseling                    | 10.3 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 90 dB(A)  |
| Sound power level (LwA)      | 101 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Side handle  
Duster  
Plastic carry case  
Front handle  
Lubricant for tool shank end