

SBE 760 (600841610) Impact drill (110-120 V / 50 - 60 Hz); Plastic Carry Case

Order no. 600841610 EAN 4007430214720



S-AUTOMATIC MECHANICAL SAFETY CILITCH Product may differ from Image

- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Thumbwheel for Speed Preselection
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the tool stop unexpectedly
- Forward and reverse rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck

Technical data

Characteristics

Rated input power	760 W
Output power	370 W
Maximum torque	24 / 9 Nm // 212 / 80 in-lbs
Drill-Ø masonry	18 mm / 23/32 "
Drill-Ø concrete	16 mm / 5/8 "
Drill Ø steel	13 / 8 mm // 1/2 / 5/16 "
Drill-Ø soft wood	40 / 25 mm // 1 5/8 / 1 "
No-load speed	0 - 1200 / 0 - 3200 rpm
Speed at rated load	800 / 2300 rpm
Maximum impact rate	58000 bpm
Gears	2
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Collar diameter	43 mm / 1 11/16 "
Drill spindle with hexagonal recess	6.35 mm / 1/4 "
Drill spindle thread	1/2 " - 20 UNF
Chuck clamping type	Keyless chuck
Weight (without power cable)	2.3 kg / 5.1 lbs
Cable length	2.5 m / 8 ft
Vibration	
Drilling in metal	3.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Impact drilling concrete	12.7 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Futuro Plus keyless chuck Plastic carry case Side handle Drilling depth guide