

## WEA 19-180 Quick RT (601095000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 601095000 EAN 4007430314307



Product may differ from Image



- The most powerful one with full 1,900 Watt for industrial processing of weld seams and a cutting depth like a large angle grinder (Ø 230 mm) with only half the weight
- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Metabo Marathon-motor with new cooling and carbon brush system for twice the service life
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Reduced vibrations for low-fatigue working thanks to Metabo VibraTech (MVT) side handle and integrated Auto-balancer
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical data

## Characteristics

Disc-Ø	180 mm // 7 "
Rated input power	1900 W
Output power	1240 W
No-load speed	8200 rpm
Speed at rated load	8200 rpm
Torque	5 Nm / 44 in-lbs
Spindle thread	M 14
Handle circumference	138 mm / 5.438 "
Weight (without power cable)	2.7 kg / 6 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	4.9 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s²
Grinding with sandpaper	4 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s²
Uncertainty of measurement K Noise emission	1.5 m/s <sup>2</sup>
	1.5 m/s² 94 dB(A)
Noise emission	

## Scope of delivery

Guard Metabo VibraTech (MVT) side handle Inner support flange M-Quick flange nut