

## **WEV 1500-125 Quick RT (601243500) Angle grinder** (220-240 V / 50 - 60 Hz); Plastic Carry Case; with speed control, quick-locking nut

Order no. 601243500  
EAN 4007430297402



Product may differ from Image



- Efficient and robust angle grinder with ergonomic soft handle for low-fatigue working, especially overhead
- Powerful and robust angle grinder with speed control and ergonomic soft handle for low-fatigue working, especially overhead
- Powerful motor with good overload capacity
- Vario Tacho Constamatic (VTC) Full-wave Electronics with Thumbwheel: for working at customised speeds to suit the application material and speeds that remain almost constant, even under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety
- Electronic soft start for smooth start-up
- Restart protection after power interruption
- Auto-stop carbon brushes to protect the motor

**Technical data****Characteristics**

|                              |                       |
|------------------------------|-----------------------|
| Disc-Ø                       | 125 mm // 5 "         |
| Rated input power            | 1500 W                |
| Output power                 | 900 W                 |
| No-load speed                | 3500 - 11000 rpm      |
| Speed at rated load          | 11000 rpm             |
| Torque                       | 4.2 Nm / 37.2 ft. lbs |
| Spindle thread               | M 14                  |
| Handle circumference         | 138 mm / 5.438 "      |
| Weight (without power cable) | 2.4 kg / 5.3 lbs      |
| Cable length                 | 4 m / 13 ft           |

**Vibration**

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 9 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 5.3 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

**Noise emission**

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 87 dB(A) |
| Sound power level (LwA)      | 98 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

**Scope of delivery**

Guard  
Side handle  
Plastic carry case  
Inner support flange  
"Quick" flange nut