

STA 18 LTX 150 BL (601502840) Cordless jigsaw 18V; metaBOX 145 L

Order no. 601502840
EAN 4061792234024



Product may differ from Image



- The power pack for demanding applications: Cordless jigsaw with maximum cutting output thanks to powerful Brushless motor and constant strokes under load
- Best ergonomics in all working positions and soft-grip surface for perfect handling and safe guidance of the saw
- Powerful Brushless motor for quick work progress and highest efficiency
- Metabo "Quick" for changing saw blades without tools and with automatic ejection
- Low-lying saw blade guidance for precise cuts
- Efficient chip blowing function for clear view of the cutting line
- Integrated LED work light, can be switched off for cuts from below without getting blinded by the light
- Restart protection: prevents unintentional start-up after battery pack change
- Long service life thanks to optimum gear and motor design and robust die-cast aluminium gear housing
- Extraction possibility by means of connecting an all-purpose vacuum cleaner
- Splinter-free and gentle sawing due to guard plate and chip break guard
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| | |
|-----------------------------|--------------------|
| Type of battery pack | LiHD |
| Battery voltage | 18 V |
| Cutting depth wood | 150 mm / 5 29/32 " |
| Cutting depth NF metal | 35 mm / 1 3/8 " |
| Cutting depth sheet steel | 10 mm / 3/8 " |
| Swivel range from / to: | - 45 / + 45 ° |
| Pendulum stroke levels | 4 |
| Strokes in idle | 1000 - 3500 rpm |
| Saw blade stroke | 26 mm / 1 1/32 " |
| Weight without battery pack | 1.9 kg / 4.2 lbs |
| Weight with battery pack | 2.5 kg / 5.5 lbs |

Vibration

| | |
|------------------------------|----------------------|
| Sawing wood | 6.1 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Sawing metal | 5.8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 88 dB(A) |
| Sound power level (LwA) | 99 dB(A) |
| Uncertainty of measurement K | 5 dB(A) |

Scope of delivery

Extraction nozzle
 Chip guard plate
 3 Jigsaw blades
 Hexagonal wrench
 metaBOX 145 L
 without battery pack, without charger
 Protective glass
 Plastic guard plate