

## Power 400-20 W OF (601546000) Compressor (230 V / 50 Hz); Cardboard box

Order no. 601546000  
EAN 4007430244888



Product may differ from Image



- Compact and mobile piston compressor for flexible use both indoors and on construction sites
- Particularly low-level noise and vibrations
- For single phase alternating current
- Designed for continuous operation with S1 motor operating mode
- Oil-free piston compressor: simple transportation and reduced service requirements
- Operating pressure can be regulated according to application by means of a pressure reducer and manometer
- Fittings and control elements protected in tubular frames and clearly visible
- Rubberised, stable wheels and pull handle for mobile use
- Cable winding mechanism
- Convenient pressure switch for good cold starting, complete with relief valve
- Overload protection: protects the motor from overheating
- Rubberised feet for optimum stability
- Attachment and transport option for Metaloc and other common storage case systems
- Crane eyelet for safe and easy transport on the construction site

## Technical data

### Characteristics

|                                                  |                                        |
|--------------------------------------------------|----------------------------------------|
| Suction rate                                     | 330 l/min / 87 gal/h                   |
| Filling capacity                                 | 200 l/min / 7.1 cfm                    |
| Effective delivery volume (at 80% max. pressure) | 185 l/min / 6.5 cfm                    |
| Maximum pressure                                 | 10 bar / 145 psi                       |
| Rated input power                                | 2.2 kW / 3 HP                          |
| Maximum speed                                    | 1400 rpm                               |
| Tank capacity                                    | 20 l / 5.3 gal                         |
| Sound pressure level (LpA)                       | 78 dB(A)                               |
| Sound power level (LwA)                          | 95 dB(A)                               |
| Dimensions                                       | 580 x 600 x 500 mm // 1.9 x 2 x 1.7 ft |
| Weight                                           | 47 kg / 103.6 lbs                      |
| Cable length                                     | 4 m / 13 ft                            |

### Noise emission

|                         |          |
|-------------------------|----------|
| Sound pressure level    | 78 dB(A) |
| Sound power level (LwA) | 95 dB(A) |

## Scope of delivery

2 Universal quick-action couplings