

KH 18 LTX BL 24 Q (601714800) Cordless hammer

18V 2x4Ah LiHD; Charger ASC 55; metaBOX 165 L; with Metabo Quick change chuck

Order no. 601714800

EAN 4061792218574



Product may differ from Image



- Extremely light and compact cordless hammer with integrated extraction interface
- Maximum drill performance, efficiency and service life thanks to brushless technology and high-performance hammer action
- Dust-free drilling with compact dust extraction ISA 24 (accessory)
- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo VibraTech (MVT): working, also continuously, in a low-fatigue manner whilst protecting the user's health
- Metabo Quick: fast, tool-free chuck for working with SDS-plus and straight shank drill bits
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Electronic soft start for precise spot-drilling
- Double safety when the drill bit jams: No kick-back thanks to the mechanic decoupling plus ultra-fast sensor-controlled shutdown
- LED work light for optimum view of the drilling site
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| | |
|-------------------------------------|------------------|
| Type of battery pack | LiHD |
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 4 Ah |
| Max. single blow energy (EPTA) | 2.2 J |
| Maximum impact rate | 4750 bpm |
| Drill-Ø concrete with hammer drills | 24 mm / 1 " |
| Drill-Ø masonry with core bits | 82 mm / 3 7/32 " |
| Drill Ø steel | 13 mm / 1/2 " |
| Drill-Ø soft wood | 30 mm / 1 3/16 " |
| No-load speed | 0 - 1280 rpm |
| Bit retainer | SDS-plus |
| Weight without battery pack | 3 kg / 6.61 lbs |

Vibration

| | |
|------------------------------|-----------------------|
| Hammer drilling concrete | 13.4 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 9.1 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 90 dB(A) |
| Sound power level (LwA) | 101 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Hammer chuck for tools with SDS-plus shank end
 Drilling depth guide
 2 LiHD Battery packs (18 V/4.0 Ah)
 Charger ASC 55 "AIR COOLED"
 metaBOX 165 L
 Keyless chuck for tools with cylindrical shank
 rubber-coated side handle