

ASR 35 M ACP (602058180) All-purpose vacuum cleaner (220-240 V / 50 - 60 Hz); Cardboard box; with Measurement of Pressure Differentials

Order no. 602058180
EAN 4007430250131



Product may differ from Image



- For extraction from the power tool in continuous mode, both on construction sites and in the workshop
- Especially suited for extracting concrete and rock dust
- Compact vacuum cleaner for liquids and dry solids with commercial registration
- Power socket for a power tool for using the automatic start-up/shut-down of the vacuum cleaner
- AutoCleanPlus: saves both costs and time thanks to automatic MPulse filter cleaning during continuous use
- If the optimum suction performance falls below a certain level, the filters are vibrated immediately
- High user protection: certified in accordance with EU standard for M class dusts
- Automatic shut-down when vacuuming liquids once the maximum fill level is reached
- Warning signal on shortfall of the minimum volume flow to protect the user
- Optimum suction power by preselection of the hose diameter
- Automatic trailing mechanism for emptying the suction hose completely
- Antistatic basic equipment prevents static charge when using appropriate accessories
- Sturdy thanks to especially large wheels and castors with wheel stop
- Cable winding mechanism
- Practical accessory case and storage area

Technical data

Characteristics

| | |
|------------------|-------------------------------------|
| Air output max. | 4380 l/min / 157 cfm |
| Vacuum | 270 hPa (mbar) / 3.6 psi |
| Filter surface | 8600 cm ² / 1333 sq.inch |
| Input power max. | 1400 W |
| Container volume | 35 l / 9 gal |
| Suction hose Ø | 35 mm / 1 3/8 " |
| Hose length | 5 m / 16 ft |
| Weight | 16 kg / 35.3 lbs |
| Cable length | 8 m / 26 ft |

Noise emission

| | |
|----------------------|----------|
| Sound pressure level | 69 dB(A) |
|----------------------|----------|

Scope of delivery

- Suction hose (Ø 35 mm / 5 m)
- 2 Polyester filter cassettes (M class)
- PE Disposal bag
- Crevice nozzle
- Floor nozzle (370 mm wide)
- Stainless steel handle bar with auxiliary air slide Ø 35 mm
- 2 Stainless steel suction tubes (Ø 35 mm, 50 cm lang)