

## ASR 35 H ACP (602059000) All-purpose vacuum cleaner

(220-240 V / 50 - 60 Hz); Cardboard box; with Electromagnetic Shaking and Measurement of Pressure Differentials

Order no. 602059000 EAN 4007430279316



Product may differ from Image



- Ideal vacuum cleaner for removal of mould and old insulation in roof and wall areas
- Ideal when sanding painted or coated wood surfaces with lead, nickel, cadmium or chromium content
- Compact vacuum cleaner for liquids and dry solids with commercial registration
- Power socket for a power tool for using the automaticalstart-up/shut-down of the vacuum cleaner
- AutoCleanPlus: saves both costs and time thanks to automatic MPulse filter cleaning during continuous use
- If the optimum suction performance falls below a certain level, the filters are vibrated immediately
- Maximum user protection: certified in accordance with EU standard for H class dusts
- Automatic shut-down when vacuuming liquids once the maximum fill level is reached
- Warning signal on shortfall of the minimum volume flow to protect the user
- Optimum suction power by preselection of the hose diameter
- Automatic trailing mechanism for emptying the suction hose completely
- Antistatic basic equipment prevents static charge when using appropriate accessories
- Sturdy thanks to especially large wheels and castors with wheel stop
- Cable winding mechanism
- Practical accessory case and storage area

## Technical data

## Characteristics

| Air output max.      | 4380 l/min / 157 cfm     |
|----------------------|--------------------------|
| Vacuum               | 270 hPa (mbar) / 3.6 psi |
| Filter surface       | 8600 cm² / 1333 sq.inch  |
| Input power max.     | 1400 W                   |
| Container volume     | 35 l / 9 gal             |
| Suction hose Ø       | 35 mm / 1 3/8 "          |
| Hose length          | 4 m / 15 ft              |
| Weight               | 16 kg / 35.3 lbs         |
| Cable length         | 8 m / 26 ft              |
| Noise emission       |                          |
| Sound pressure level | 69 dB(A)                 |

## Scope of delivery

Antistatic suction hose (Ø 35 mm / 4 m) 2 Plastic suction tubes 2 HEPA polyester filter cassettes PE Disposal bag Crevice nozzle Floor nozzle (300 mm wide) Connection bush Ø 41/48 mm Handle adapter