

## W 18 L 9-125 (602247510) Cordless angle grinder 18V 2x4Ah Li-Power; Charger ASC 55; metaBOX 165 L

Order no. 602247510  
EAN 4061792207608



Product may differ from Image



- Robust angle grinder with powerful motor and slim design for universal applications
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery pack change
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                 |
|-----------------------------|-----------------|
| Type of battery pack        | Li-Power        |
| Battery pack capacity       | 2 x 4 Ah        |
| Battery voltage             | 18 V            |
| Disc-Ø                      | 125 mm / 5 "    |
| Max. cutting depth          | 34 / 1.339      |
| No-load speed               | 8500 rpm        |
| Spindle thread              | M 14            |
| Handle circumference        | 191 mm / 7.52 " |
| Weight without battery pack | 1.6 kg          |
| Weight with battery pack    | 2.3 kg          |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 5 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 86 dB(A) |
| Sound power level (LwA)      | 97 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Guard  
Side handle  
Flat-pin spanners  
2 Li-Power battery packs (18 V/4.0 Ah)  
Charger ASC 55 "AIR COOLED"  
metaBOX 165 L  
Inner support flange  
Nut with two holes