

SB 18 LTX-3 BL I (602356650) Cordless hammer drill
18V 2x5.2Ah Li-Power; Charger ASC 55 (220-240 V / 50 - 60 Hz); metaBOX 145 L

Order no. 602356650
 EAN 4007430298249



Product may differ from Image



- Brushless 3-speed cordless hammer drill with maximum power for demanding applications
- Third speed setting with high torque (max. 3,800/min) for extended range of application and even faster drilling progress
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Robust, durable gear housing made from aluminium die-cast
- Spindle with magnetic hexagon recess for screwdriver bits for working without chuck
- Powerful Brushless motor for greatest efficiency and long battery pack runtime
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- High-performance impact mechanism for optimum drilling performance
- Euro collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- With handy belt hook and bit case which can be fixed either on the right or left side
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

Type of battery pack	Li-Power
Battery voltage	18 V
Battery pack capacity	2 x 5.2 Ah
Maximum torque, soft	60 Nm / 531 in-lbs
Pulse torque	65 Nm / 48 in-lbs
Maximum torque, hard	120 Nm / 1062 in-lbs
Adjustable torque	1 - 20 Nm // 9 - 177 in-lbs
Drill-Ø masonry	16 mm / 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	65 mm / 2 1/2 "
No-load speed	0 - 500 / 0 - 2050 / 0 - 3800 rpm
Maximum impact rate	32300 bpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Collar diameter	43 mm / 1 11/16 "
Weight without battery pack	1.9 kg / 4.2 lbs
Weight with battery pack	2.6 kg / 5.7 lbs

Vibration

Drilling in metal	3.8 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Impact drilling concrete	17.7 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	71 dB(A)
Sound power level (LwA)	82 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Futuro Plus keyless chuck with metal sleeve
 2 Li-Power battery packs (18 V/5.2 Ah)
 Charger ASC 55 "AIR COOLED"
 metaBOX 145 L
 Side handle
 Belt hook and bit case