

## BS 18 LTX BL I (602358840) Cordless drill / screwdriver 18V; metaBOX 145 L

Order no. 602358840

EAN 4061792188143



Product may differ from Image



- Brushless drill/screwdriver with maximum power for demanding applications
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Powerful Brushless motor for greatest efficiency and long battery pack runtime
- Precision Stop: electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Euro collar (Ø 43 mm) for versatile use
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                             |
|-----------------------------|-----------------------------|
| Battery voltage             | 18 V                        |
| Maximum torque, soft        | 65 Nm / 575 ft. lbs         |
| Pulse torque                | 65 Nm / 575 in-lbs          |
| Maximum torque, hard        | 130 Nm / 1151 ft. lbs       |
| Adjustable torque           | 1 - 20 Nm // 9 - 177 in-lbs |
| Drill Ø steel               | 13 mm / 1/2 "               |
| Drill-Ø soft wood           | 68 mm / 2.68 "              |
| No-load speeds              | 0 - 550 / 0 - 2000 rpm      |
| Chuck capacity              | 1.5 - 13 mm // 1/16 - 1/2 " |
| Collar diameter             | 43 mm / 1 11/16 "           |
| Weight without battery pack | 1.7 kg / 3.7 lbs            |
| Weight with battery pack    | 2.2 kg / 4.9 lbs            |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Drilling in metal            | 2.2 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 76 dB(A) |
| Sound power level (LwA)      | 87 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Keyless chuck  
 Belt hook and bit case  
 metaBOX 145 L  
 Bit holder  
 Side handle