

## SB 18 LTX BL I (602360500) Cordless hammer drill

18V 2x4Ah Li-Power; Charger ASC 55 (220-240 V / -); metaBOX 145 L

Order no. 602360500  
EAN 4061792187849



Product may differ from Image



- Brushless hammer drill with maximum power for demanding applications
- Hammer drill function for drilling in masonry
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

## Technical data

### Characteristics

|                             |                             |
|-----------------------------|-----------------------------|
| Type of battery pack        | Li-Power                    |
| Battery voltage             | 18 V                        |
| Battery pack capacity       | 2 x 4 Ah                    |
| Maximum torque, soft        | 65 Nm / 575 ft. lbs         |
| Pulse torque                | 65 Nm / 575 in-lbs          |
| Maximum torque, hard        | 130 Nm / 1151 ft. lbs       |
| Adjustable torque           | 1 - 20 Nm // 9 - 177 in-lbs |
| Drill-Ø masonry             | 16 mm / 5/8 "               |
| Drill Ø steel               | 13 mm / 1/2 "               |
| Drill-Ø soft wood           | 68 mm / 2.68 "              |
| No-load speed               | 0 - 550 / 0 - 2000 rpm      |
| Maximum impact rate         | 38000 bpm                   |
| Chuck capacity              | 1.5 - 13 mm // 1/16 - 1/2 " |
| Collar diameter             | 43 mm / 1 11/16 "           |
| Weight without battery pack | 1.8 / 4                     |
| Weight with battery pack    | 2.5 kg / 5.5 lbs            |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Drilling in metal            | 2.6 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Impact drilling concrete     | 16.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.7 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 92 dB(A)  |
| Sound power level (LWA)      | 103 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Keyless chuck  
 2 Li-Power battery packs (18 V/4.0 Ah)  
 Charger ASC 55 "AIR COOLED"  
 metaBOX 145 L  
 Side handle  
 Belt hook and bit case